## CLARION<sup>®</sup> Food Grade FR Fluid

clarion.

	<ul> <li>Food grade water-glycol fire-resistant hydraulic fluid.</li> <li>Designed for food process applications such as fryers, ovens, cookers, and others where a fire resistant hydraulic fluid is required or desired.</li> </ul>
FEATURES & BENEFITS	<ul> <li>Very high viscosity index, low pour point, and excellent heat transfer properties allow use over a wide range of applications and operating conditions.</li> <li>Demonstrates lower overall system temperatures, thereby providing better system performance.</li> <li>Demonstrated lower power consumption resulting in additional energy savings.</li> <li>Approved by Factory Mutual under Group 1 (HFC) as a less flammable fluid. Approval number 3021353.</li> <li>Meets the requirements of U.S. FDA regulation 21 CFR 178.3570 for incidental food contact.</li> <li>NSF H1 registered for use in food processing plants under the jurisdiction of the USDA.</li> </ul>
APPLICATIONS	<ul> <li>Designed for food process applications such as fryers, ovens, cookers and others where a fire resistant hydraulic fluid is desired.</li> <li>Note: The water concentration in the fluid must be monitored and adjusted as needed to ensure proper fire resistance properties.</li> </ul>

CITGO Petroleum Corporation Houston, Texas Customer Service Line 1-800-331-4068 LubesCS@CITGO.com Product Answer Line 1-800-248-4684 lubeshelp@CITGO.com

Online at www.ClarionLubricants.com

## PROPERTIES



## Typical Properties for CLARION® Food Grade FR Fluid:

ISO Grade	46
Commodity Code	632503009
Specific Gravity @ 60°F ASTM D1298	1.06
Density, lbs/gallon	8.84
Color	Water White
Appearance	Slight Haze
Viscosity, cSt at 40°C ASTM D445	46
Pour Point, °C (°F) ASTM D97	-50 (-58)
Flash Point, COC, °C (°F) ASTM D92	None
Copper Corrosion ASTM D130	1A
рН	8.9
Vane Pump Wear Test, mg wear	<25
Rust Test ASTM D665A	Pass
Bulk Modulus, kPa ASTM D6793	2.189 x 10 <sup>6</sup>
NSF Registered (Registration Number)	H1 (134001)
FDA, 21 CFR 178.3570	<ul> <li></li> </ul>

CLARION® is a registered trademark of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners. Values shown are typical values only and do not constitute a specification. The information contained herein is subject to change without notice.

CITGO Petroleum Corporation Houston, Texas Customer Service Line 1-800-331-4068 LubesCS@CITGO.com Product Answer Line 1-800-248-4684 lubeshelp@CITGO.com

Online at www.ClarionLubricants.com