

# CLARION® ClariPac Oils



## OVERVIEW



- Refined by high pressure hydrotreating to produce a technical grade white mineral oil of the highest quality, stabilized with Vitamin E.

## FEATURES & BENEFITS



- Exceeds the requirements of U.S. FDA regulation 21 CFR 178.3620 (b), for use as a component of non-food articles in contact with food for human consumption.
- NSF H1 Registered for use in food processing plants under the jurisdiction of the USDA.
- NSF/ANSI/CAN Standard 61: Drinking Water System Components - Health Effects (Grades 90, 200 and 350 only).




Certified to  
NSF/ANSI/CAN  
Standard 61

Claripac 90, 200, 350 (only)

## APPLICATIONS



- Drawing, stamping, forming, and rolling of aluminum foil used in food packaging.
- As a defoamer in the manufacture of paper and adhesives intended for food packaging.
- Lubrication of textile fibers/fabric used to process food.
- As a plasticizer for rubber used on conveyor belts, hoses, and rollers.
- As a lubricant cleaner and rust preventive for machinery and other equipment in food processing plants.
- As a base oil for the formulation of gel candles.
- As a dust control agent for aggregate materials as well as grains not intended for human consumption such as animal feeds. Not for use in dust control applications for grains intended for human consumption, which require a product meeting US FDA regulation 21 CFR 178.878 such as Clarion Food Grade White Mineral Oils.
- As a slitter oil or other applications where non-staining is critical.
- As a drip oil for water well pump lubrication systems where an NSF H1 food grade lubricant is required or desired. Always consult State and local regulatory agencies requirements for water system lubricant requirements.
- Grades 90, 200, and 350 are recommended for water well pump and other potable water system lubrication applications where an NSF/ANSI/CAN Standard 61 certified lubricant is required or desired.

**PROPERTIES****Typical Properties for CLARION ClariPac Oils:**

	Clarion ClariPac 70	Clarion ClariPac 90	Clarion ClariPac 200	Clarion ClariPac 350	Clarion ClariPac 500
Material Code	633531009	633532009	633533009	633539009	633540009
Gravity, ASTM D4052, °API	34	33.4	32	32	31
Density, lbs/gallon	7.1	7.14	7.23	7.23	7.25
Flash Point, °C (°F) ASTM D92	180 (356)	190 (374)	218 (424)	246 (475)	246 (475)
Pour Point, °C (°F) ASTM D97	-23 (-9)	-27 (-17)	-12 (10)	-12 (10)	-9 (16)
Viscosity					
cSt at 40°C	12.6	16.0	37.5	65.04	107
cSt at 100°C	3	3.5	6	8.6	12
SUS @ 100°F	72	87	193	337	562
Color, Saybolt, ASTM D156	+20	+20	+20	+20	+20
NSF/ANSI/CAN Standard 61 Certified	—	✓	✓	✓	—
FDA 21 CFR 178.3620 (b)	✓	✓	✓	✓	✓
NSF	H1	H1	H1	H1	H1

CLARION is a registered trademark of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners. Values shown are typical values only and do not constitute a specification. The information contained herein is subject to change without notice.